



MODEL 70

The new standard for the CRT terminal industry from the first independent commercial CRT manufacturer.

- Microprocessor controlled
 - 80 characters X 25 lines
 - Upper/Lower case
 - Eight function keys
 - Tilt/Swivel screen
- AND MUCH MORE



*Stability
Age
Beauty*

TEC, Incorporated

2727 N. FAIRVIEW AVENUE • TUCSON, ARIZONA USA 85705 • (602) 792-2230 • TWX 910-952-1377

AN EQUAL OPPORTUNITY EMPLOYER M/F, COMMITTED TO AFFIRMATIVE ACTION — A TEC INCORPORATED CORPORATE POLICY

MODEL 70 SPECIFICATIONS

The Model 70 is a Microprocessor-based, TTY Compatible CRT Display Terminal, offering small size, exceptionally good looks, a very competitive price, and a host of features that make it the most desirable CRT display on the market today.

BASIC MACHINE FEATURES ARE AS FOLLOW:

- Small size: Monitor - 14.25" W x 15.25" D x 17.25" H (361.95 W x 387.35 D x 438.15 H)
Keyboard - 15.75" W x 6.75" D x 2.75" H (400.05 W x 171.45 D x 69.85 H)
- 8 x 10 dot matrix character field, providing big (.20" x .08") characters in an 80 character x 25 line format, allowing 126 displayable ASCII Codes, and generation of all 128-ASCII Codes, which means upper/lower case, line and bar drawings, plus display of Control Codes is standard
- 12" diagonal P-4 phosphor tube with non-glare screen
- 60 Hz, 100, 115 or 230 VAC operation
- Conversational operation in half or full duplex, asynchronous
- Blinking underline or blinking block cursor
- Brightness and Contrast Controls, plus TEC's exclusive CRT saver, which automatically reduces the screen intensity if no data is transmitted or received for five minutes
- Speeds of 50 - 9600 baud, external switch, and RS-232-C or TTL interfaces
- 10 or 11 bit word size, with odd, even or mark parity
- Two RS-232-C I/O ports, selectable by the operator
- Absolute cursor reading and loading
- Composite video output for use with remote monitors
- Detachable keyboard with repeat on all keys, and N-key rollover
- Eight function keys, programmed to the first two columns of the ASCII Code Chart
- Tilt/swivel screen

C.N. Rood B.V.

Postbus 42 - Tel. 996360*
RIJSWIJK (Z.H.) - Nederland

NOW LOOK AT THESE OPTIONS:

- Edit/Attribute Option Package - provides for buffered operation, reduced intensity, inverse video, blinking, protected fields, security (non-displayed) fields, or any combination of the preceding. Also, insert/delete line, insert/delete character, erase end of line, erase end of field, erase end of page, transmit unprotected data, transmit unprotected and protected data, transmit partial page, transmit line, tab, back tab, auto tab, columnar tab
- Polling interfaces (TEC, Univac, Honeywell or Burroughs protocols)
- Data-Panel[®] allows the display of 16 fixed message indicators
- Special programming of function keys
- Serial/Parallel hard copy adapter
- Paging memory - 1 or 2 pages
- Synchronous interfaces
- Current loop interface
- P-31 monitor
- Numeric keypad
- 50 Hz, 100, 115 or 230 VAC operation

In addition to the Model 70, TEC manufactures many other fine peripheral products which include the DISCO-TEC[™] Floppy Disc Memory System, the Model 1200 Thermal Printer and a variety of 16 different CRT terminals.

3340 5-78



TEC, Incorporated

2727 N. FAIRVIEW AVE., TUCSON, AZ. USA 85705
(602) 792-2230 - TWX 910-952-1377

I am interested in the Model 70: _____

Call me _____ Arrange demonstration _____

Name _____ Title _____

Company _____ Phone _____

Address _____

City _____ State _____ Zip _____